

SOLA[®]

SERIES



SW-650

Architectural In-Wall Speakers

Features

- Flush mount architectural in-wall speaker
- High efficiency design for maximum amplifier performance
- Aimable titanium tweeter for best high frequency imaging
- Designed for digital audio reproduction
- Moisture resistant speaker cone for use in bathrooms and other high humidity environments
- Powder coated aluminum grille prevents rust and corrosion
- Removable grille scrim cloth for added protection against dust and debris
- Ideal for ZON Whole House Digital Audio Controller/Amplifiers
- Sonically matched to Sola SC-650 in-ceiling speakers
- Easy to install with simple tools using quick mount tabs
- Mounting template and paint shield included
- Paintable grille and escutcheon

Key Specifications

Speaker Type	Two-way in-wall
Frequency Response	30 Hz - 20 kHz
Recommended Power	5 - 100 w (RMS)
Impedance	8 Ohms (Nominal)
Efficiency	89 dB
Woofer	6.5" Polypropylene with polyurethane edge and dust cap
Tweeter	0.75" Titanium Eyeball
Crossover	12 dB / Octave
Warranty	Limited, 5 Year
Optional Hardware	RIK-650W Pre-Construction Bracket (Pair)

Oxmoor Corporation, LLC
309A Cahaba Valley Parkway North
Indian Springs, AL 35124
Telephone: 800-262-6898
Internet: www.zonaudio.com

Optimized for

ZON[®]
Whole House
Digital Audio